


Aluminium-U-Profile

EN AW-6060 T66 (AlMgSi0,5)

EN 573-3 / 755-2 / 755-1 / 755-9

■ (DIN 1725 / 1748 Teil 1 / 1748 Teil 2 / 1748 Teil 3 / 9714)

■ in Herstellungslängen von ca. 6 m



h x b x s in mm	kg/mtr.
10,0 x 10,0 x 2,0	0,140
14,0 x 16,0 x 2,0	0,227
15,0 x 15,0 x 2,0	0,221
20,0 x 15,0 x 2,0	0,256
20,0 x 20,0 x 2,0	0,302
20,0 x 40,0 x 2,5	0,641
25,0 x 25,0 x 2,0	0,383
25,0 x 25,0 x 3,0	0,590
30,0 x 20,0 x 2,0	0,356
30,0 x 30,0 x 2,0	0,464
30,0 x 30,0 x 3,0	0,680
35,0 x 25,0 x 2,0	0,545

h x b x s in mm	kg/mtr.
35,0 x 35,0 x 3,0	0,802
40,0 x 20,0 x 2,0	0,410
40,0 x 20,0 x 2,5	0,506
40,0 x 30,0 x 3,0	0,761
40,0 x 40,0 x 2,5	0,776
40,0 x 40,0 x 3,0	0,951
40,0 x 40,0 x 4,0	1,245
45,5 x 12,0 x 2,5	0,435
50,0 x 30,0 x 3,0	0,842
50,0 x 50,0 x 3,0	1,201
50,0 x 50,0 x 5,0	1,946
55,0 x 45,0 x 2,0	0,761

h x b x s in mm	kg/mtr.
60,0 x 20,0 x 2,0	0,518
60,0 x 40,0 x 2,5	0,911
65,0 x 25,0 x 2,5	0,743
65,0 x 55,0 x 2,5	1,148
80,0 x 30,0 x 3,0	1,085
80,0 x 40,0 x 3,0	1,247
80,0 x 40,0 x 4,0	1,641
86,0 x 40,0 x 3,0	1,296
100,0 x 20,0 x 2,0	0,734
100,0 x 40,0 x 3,0	1,409
100,0 x 50,0 x 8,5	4,199
106,0 x 40,0 x 3,0	1,458