


## Aluminium-Winkelprofile

**EN AW 6060 T66 (AlMgSi0,5)**

**EN 573-3/755-2/755-1/755-9**

- (DIN 1725/1748 Teil 1/1748 Teil 2/1748 Teil 3/1771)
- in Herstellungslängen von ca. 6 m

- gleichschenkelig



axaxs in mm	kg/mtr.	axaxs in mm	kg/mtr.	axaxs in mm	kg/mtr.
10 x 10 x 2,0	0,097	40 x 40 x 2,0	0,421	60 x 60 x 6,0	1,847
15 x 15 x 2,0	0,151	40 x 40 x 3,0	0,624	60 x 60 x 8,0	2,419
15 x 15 x 3,0	0,219	40 x 40 x 4,0	0,821	60 x 60 x 10,0	2,970
20 x 20 x 2,0	0,205	40 x 40 x 5,0	1,013	70 x 70 x 6,0	2,171
20 x 20 x 3,0	0,300	50 x 50 x 2,0	0,571	80 x 80 x 3,0	1,271
25 x 25 x 2,0	0,259	50 x 50 x 3,0	0,785	80 x 80 x 4,0	1,685
25 x 25 x 3,0	0,381	50 x 50 x 4,0	1,037	80 x 80 x 6,0	2,295
25 x 25 x 4,0	0,497	50 x 50 x 5,0	1,283	80 x 80 x 8,0	3,283
30 x 30 x 2,0	0,313	50 x 50 x 6,0	1,523	100 x 100 x 4,0	2,117
30 x 30 x 3,0	0,462	50 x 50 x 8,0	1,987	100 x 100 x 6,0	3,143
30 x 30 x 4,0	0,605	60 x 60 x 2,0	0,630	100 x 100 x 8,0	4,380
30 x 30 x 5,0	0,743	60 x 60 x 2,5	0,793	100 x 100 x 10,0	5,130
35 x 35 x 3,0	0,543	60 x 60 x 4,0	1,253		
35 x 35 x 4,0	0,713	60 x 60 x 5,0	1,599		