


## Aluminium-Vierkantrohre

**EN AW 6060 T66 (AlMgSi0,5)**

**EN 573-3/755-2/755-1**

- (DIN 1725/1748 Teil 1/1748 Teil 2/1748 Teil 3/1748 Teil 4)
- in Herstellungslängen von ca. 6 m



ax ax s in mm	kg/mtr.	ax ax s in mm	kg/mtr.	ax ax s in mm	kg/mtr.
15 x 15 x 2,0	0,281	34 x 34 x 3,0	1,004	50 x 50 x 3,0	1,522
20 x 20 x 1,5	0,300	35 x 35 x 2,0	0,734	50 x 50 x 4,0	1,987
20 x 20 x 2,0	0,389	35 x 35 x 3,0	1,068	60 x 60 x 3,0	1,847
20 x 20 x 3,0	0,550	40 x 40 x 2,0	0,821	60 x 60 x 4,0	2,419
25 x 25 x 2,0	0,497	40 x 40 x 2,5	1,013	70 x 70 x 4,0	2,851
25 x 25 x 3,0	0,713	40 x 40 x 3,0	1,199	80 x 80 x 3,0	2,495
30 x 30 x 2,0	0,605	40 x 40 x 4,0	1,555	80 x 80 x 4,0	3,283
30 x 30 x 3,0	0,875	50 x 50 x 2,0	1,037	100 x 100 x 4,0	4,147