


Aluminium-Rechteckrohre

EN AW 6060 T66 (AlMgSi0,5)

■ in Herstellungslängen von ca. 6 m



axbxs in mm	kg/mtr.	axbxs in mm	kg/mtr.	axbxs in mm	kg/mtr.
20 x 15 x 2,0	0,350	50 x 40 x 4,0	1,771	100 x 25 x 1,8	1,180
25 x 20 x 2,0	0,520	60 x 20 x 2,0	0,860	100 x 40 x 2,0	1,470
30 x 10 x 1,5	0,300	60 x 25 x 2,0	0,901	100 x 40 x 3,0	2,170
30 x 15 x 2,0	0,443	60 x 30 x 2,0	0,956	100 x 40 x 4,0	2,851
30 x 20 x 2,0	0,497	60 x 30 x 3,0	1,361	100 x 50 x 2,0	1,580
30 x 20 x 3,0	0,734	60 x 34 x 3,0	1,426	100 x 50 x 4,0	3,067
34 x 20 x 2,0	0,540	60 x 40 x 2,5	1,283	100 x 60 x 2,0	1,735
40 x 20 x 2,0	0,605	60 x 40 x 3,0	1,523	100 x 60 x 4,0	3,290
40 x 20 x 2,5	0,743	60 x 40 x 4,0	1,987	120 x 30 x 2,0	1,624
40 x 20 x 3,0	0,875	60 x 50 x 3,0	1,685	120 x 40 x 4,0	3,283
40 x 30 x 2,0	0,734	80 x 20 x 2,0	1,040	120 x 50 x 4,0	3,499
40 x 30 x 2,5	0,878	80 x 30 x 3,0	1,683	120 x 60 x 3,0	2,820
40 x 30 x 4,0	1,339	80 x 40 x 2,0	1,270	120 x 60 x 4,0	3,800
50 x 20 x 2,0	0,713	80 x 40 x 3,0	1,847	120 x 80 x 3,0	3,310
50 x 20 x 4,0	1,339	80 x 40 x 4,0	2,419	140 x 40 x 4,0	3,710
50 x 25 x 2,0	0,770	80 x 50 x 4,0	2,635	150 x 40 x 4,0	3,931
50 x 30 x 3,0	1,199	80 x 60 x 4,0	2,850	150 x 50 x 4,0	4,147
50 x 34 x 3,0	1,264	100 x 18 x 2,0	1,231	180 x 50 x 4,0	4,795
50 x 40 x 2,5	1,148	100 x 20 x 2,0	1,290	200 x 50 x 4,0	5,227