

# Aluminium-Rundrohre

**EN AW 6060 T66 (AlMgSi0,5)**

**EN 573-3/755-2/755-1/755-5**

- (DIN 1725/1747 Teil 1/1747 Teil 2/1770)
- in Herstellungslängen von ca. 6 m



d x s in mm	kg/mtr.
Ø 6 x 1,0	0,042
Ø 8 x 1,0	0,060
Ø 10 x 1,0	0,076
Ø 10 x 1,5	0,108
Ø 12 x 1,0	0,093
Ø 12 x 2,0	0,170
Ø 15 x 1,0	0,119
Ø 16 x 1,0	0,127
Ø 16 x 2,0	0,238
Ø 18 x 2,0	0,272
Ø 18 x 4,0	0,475
Ø 20 x 1,0	0,161
Ø 20 x 2,0	0,306
Ø 20 x 3,0	0,433
Ø 20 x 5,0	0,636
Ø 25 x 1,0	0,204
Ø 25 x 2,0	0,390
Ø 25 x 3,0	0,560
Ø 25 x 5,0	0,848

d x s in mm	kg/mtr.
Ø 30 x 1,0	0,246
Ø 30 x 2,0	0,475
Ø 30 x 3,0	0,687
Ø 32 x 1,5	0,387
Ø 35 x 2,0	0,560
Ø 35 x 2,5	0,689
Ø 35 x 3,0	0,814
Ø 40 x 2,0	0,645
Ø 40 x 2,5	0,795
Ø 40 x 3,0	0,942
Ø 40 x 5,0	1,485
Ø 43 x 3,0	1,020
Ø 45 x 3,0	1,069
Ø 50 x 2,0	0,814
Ø 50 x 2,5	1,007
Ø 50 x 3,0	1,196
Ø 50 x 5,0	1,908
Ø 55 x 2,5	1,130

d x s in mm	kg/mtr.
Ø 60 x 2,0	0,984
Ø 60 x 3,0	1,450
Ø 60 x 4,0	1,900
Ø 60 x 5,0	2,333
Ø 62 x 7,0	4,365
Ø 63 x 4,0	2,002
Ø 65 x 5,0	2,545
Ø 70 x 3,0	1,705
Ø 70 x 4,0	2,239
Ø 70 x 5,0	2,757
Ø 76 x 3,0	1,858
Ø 80 x 2,0	1,362
Ø 80 x 3,0	1,959
Ø 80 x 5,0	3,181
Ø 90 x 5,0	3,613
Ø 100 x 2,5	2,068
Ø 100 x 3,0	2,468
Ø 100 x 5,0	4,029
Ø 100 x 6,0	4,784