

Aluminium-Rundrohre

EN AW-6082 T6 (AlMgSi1)

EN 755-1 / 755-2 / 755-7

■ (DIN 1746-1)

■ in Herstellungslängen von ca. 4-6 m



D x s in mm	kg/mtr.
Ø 20 x 5	0,648
Ø 25 x 5	0,864
Ø 30 x 5	1,080
Ø 40 x 5	1,512
Ø 40 x 10	2,592
Ø 50 x 5	1,944
Ø 50 x 10	3,456
Ø 50 x 15	4,450
Ø 60 x 5	2,376
Ø 60 x 10	4,320
Ø 60 x 15	5,831
Ø 60 x 20	6,780
Ø 70 x 10	5,183
Ø 70 x 15	7,000
Ø 70 x 20	8,639

D x s in mm	kg/mtr.
Ø 80 x 10	6,047
Ø 80 x 15	8,423
Ø 80 x 20	10,367
Ø 90 x 10	6,911
Ø 90 x 15	9,719
Ø 90 x 20	12,100
Ø 100 x 10	7,775
Ø 100 x 15	11,015
Ø 100 x 20	13,823
Ø 100 x 30	18,142
Ø 120 x 10	9,503
Ø 120 x 15	13,607
Ø 120 x 20	17,278

D x s in mm	kg/mtr.
Ø 130 x 10	10,367
Ø 130 x 20	19,006
Ø 140 x 10	11,231
Ø 140 x 20	20,734
Ø 150 x 10	12,095
Ø 150 x 20	22,462
Ø 160 x 10	12,959
Ø 160 x 15	18,790
Ø 160 x 20	24,190
Ø 170 x 20	25,500
Ø 180 x 10	14,687
Ø 180 x 20	27,645
Ø 200 x 10	16,414
Ø 200 x 15	23,974
Ø 200 x 20	31,101