

Kunststoff-Rundrohre

PMMA Acryl xt (Polymethylmethacrylat)

- Lagerlängen: 2000 mm
- Farben: transparent ⊕



D x d mm	Wandstärke in mm	PMMA kg/mtr.
Ø 8 x 4	2	0,048 ⊕
Ø 10 x 8	1	0,035 ⊕
Ø 10 x 7	1,5	0,049 ⊕
Ø 10 x 6	2	0,061 ⊕
Ø 12 x 8	2	0,077 ⊕
Ø 12 x 6	3	0,104 ⊕
Ø 15 x 11	2	0,100 ⊕
Ø 16 x 12	2	0,108 ⊕
Ø 20 x 16	2	0,138 ⊕
Ø 20 x 14	3	0,196 ⊕
Ø 25 x 21	2	0,177 ⊕
Ø 25 x 19	3	0,253 ⊕
Ø 30 x 26	2	0,215 ⊕
Ø 30 x 24	3	0,311 ⊕
Ø 30 x 20	5	0,480 ⊕
Ø 38 x 32	3	0,403 ⊕
Ø 40 x 36	2	0,292 ⊕
Ø 40 x 34	3	0,426 ⊕
Ø 40 x 32	4	0,553 ⊕
Ø 40 x 30	5	0,672 ⊕
Ø 50 x 46	2	0,369 ⊕
Ø 50 x 44	3	0,541 ⊕
Ø 50 x 42	4	0,706 ⊕
Ø 50 x 40	5	0,864 ⊕
Ø 60 x 56	2	0,445 ⊕
Ø 60 x 54	3	0,656 ⊕
Ø 60 x 52	4	0,860 ⊕
Ø 60 x 50	5	1,056 ⊕

D x d mm	Wandstärke in mm	PMMA kg/mtr.
Ø 70 x 64	3	0,772 ⊕
Ø 70 x 60	5	1,248 ⊕
Ø 80 x 74	3	0,887 ⊕
Ø 80 x 70	5	1,439 ⊕
Ø 90 x 84	3	1,019 ⊕
Ø 90 x 80	5	1,631 ⊕
Ø 100 x 94	3	1,117 ⊕
Ø 100 x 90	5	1,823 ⊕
Ø 110 x 104	3	1,232 ⊕
Ø 110 x 100	5	2,015 ⊕
Ø 120 x 114	3	1,350 ⊕
Ø 120 x 110	5	2,210 ⊕
Ø 134 x 128	3	1,510 ⊕
Ø 134 x 124	5	2,480 ⊕
Ø 150 x 144	3	1,690 ⊕
Ø 150 x 140	5	2,780 ⊕
Ø 180 x 172	4	2,700 ⊕
Ø 200 x 194	3	2,270 ⊕
Ø 200 x 192	4	3,010 ⊕
Ø 200 x 190	5	3,740 ⊕
Ø 250 x 240	5	4,700 ⊕

Weitere Abmessungen auf Anfrage.